
STATEMENT

Posted by [CyberMax](#) on Sun, 09 Jul 2023 23:22:23 GMT

[View Forum Message](#) <> [Reply to Message](#)

```
EXECUTE BLOCK
RETURNS (TEXT_EXCEPTION VARCHAR(1024))
AS
BEGIN
    BEGIN
        EXECUTE STATEMENT 'execute block as begin EXCEPTION EXC$CHECK_DATA "there
exception"; end';
    END
    WHEN ANY DO
    BEGIN
        :TEXT_EXCEPTION = RDB$ERROR(MESSAGE);
        SUSPEND;
    END
END
```

```
exception 2
EXC$CHECK_DATA
There exception
At block line: 1, col: 24
At block line: 6, col: 9
```

```
EXECUTE BLOCK
RETURNS (TEXT_EXCEPTION VARCHAR(1024))
AS
BEGIN
    BEGIN
        EXECUTE STATEMENT 'execute block as begin EXCEPTION EXC$CHECK_DATA

    END
    WHEN ANY DO
    BEGIN
        :TEXT_EXCEPTION = RDB$ERROR(MESSAGE);
        SUSPEND;
    END
END
```

Arithmetic overflow or division by zero has occurred.

arithmetic exception, numeric overflow, or string truncation.
Cannot transliterate character between character sets.
At block line: 10, col: 9.

STATEMENT

Posted by [Dmitry Kovalenko](#) on Mon, 10 Jul 2023 06:58:32 GMT

[View Forum Message](#) <> [Reply to Message](#)

EXECUTE BLOCK

RETURNS (TEXT_EXCEPTION VARCHAR(1024) CHARACTER SET NONE)

STATEMENT

Posted by [CyberMax](#) on Mon, 10 Jul 2023 07:06:41 GMT

[View Forum Message](#) <> [Reply to Message](#)


STATEMENT

Posted by [Dmitry Kovalenko](#) on Mon, 10 Jul 2023 07:19:19 GMT

[View Forum Message](#) <> [Reply to Message](#)

File Attachments

1) 2023_07_10-001--fb4-exception.PNG, downloaded 1002 times



The screenshot shows a database query window with the following SQL code:

```
CREATE EXCEPTION EXC$CHECK_DATA '-----';  
  
EXECUTE BLOCK  
RETURNS (TEXT_EXCEPTION VARCHAR(1024))  
AS  
BEGIN  
BEGIN  
EXECUTE STATEMENT 'execute block as begin EXCEPTION EXC$CHECK_DATA "кыкы"; end';  
END  
WHEN ANY DO  
BEGIN  
:TEXT_EXCEPTION = RDB$ERROR(MESSAGE);  
SUSPEND;  
END  
END  
|
```

Below the code is a table with the following data:

Row Handle	TEXT_EXCEPTION
0x00000011	exception 4EXC\$CHECK_DATAкыкыAt block line: 1, col: 24At block line: 6, col: 1

STATEMENT

Posted by [Dmitry Kovalenko](#) on Mon, 10 Jul 2023 07:47:08 GMT

[View Forum Message](#) <> [Reply to Message](#)

_utf8.

File Attachments

1) [2023_07_10-002--fb4-exception.PNG](#), downloaded 942 times



```
EXECUTE BLOCK
RETURNS (TEXT_EXCEPTION VARCHAR(1024) CHARACTER SET UTF8)
AS
BEGIN
BEGIN
EXECUTE STATEMENT _utf8 'execute block as begin EXCEPTION EXC$CHECK_DATA "кыкы"; en
END
WHEN ANY DO
BEGIN
:TEXT_EXCEPTION = RDB$ERROR(MESSAGE);
SUSPEND;
END
END
```

Row Handle	TEXT_EXCEPTION
0x00000011	exception 4EXC\$CHECK_DATAкыкыAt block line: 1, col: 24At block line: 6, col:

2) [2023_07_10-003--fb4-exception.PNG](#), downloaded 999 times



Rowset: LCPI OLE DB Provider for InterBase [v5] [Prof] (D:\DATABASE\FB_04_0_0\IBP_TEST_F

```
EXECUTE BLOCK
RETURNS (TEXT_EXCEPTION VARCHAR(1024) CHARACTER SET WIN1251)
AS
BEGIN
BEGIN
EXECUTE STATEMENT _utf8 'execute block as begin EXCEPTION EXC$CHECK_DATA "кыкы"; en
END
WHEN ANY DO
BEGIN
:TEXT_EXCEPTION = RDB$ERROR(MESSAGE);
SUSPEND;
END|
END
```

Row Handle	TEXT_EXCEPTION
0x00000011	exception 4EXC\$CHECK_DATAкыкыAt block line: 1, col: 24At block line: 6, col:

3) [2023_07_10-004--fb4-exception.PNG](#), downloaded 971 times

```
EXECUTE BLOCK
RETURNS (TEXT_EXCEPTION VARCHAR(1024))
AS
BEGIN
BEGIN
EXECUTE STATEMENT _utf8 'execute block as begin EXCEPTION EXC$CHECK_DATA "кыкы"; en
END
WHEN ANY DO
BEGIN
:TEXT_EXCEPTION = RDB$ERROR(MESSAGE);
SUSPEND;
END
END
```

Row Handle	TEXT_EXCEPTION
0x00000011	exception 4EXC\$CHECK_DATAⵉCfPⵉCfAt block line: 1, col: 24At block line:

STATEMENT

Posted by [Dmitry Kovalenko](#) on Mon, 10 Jul 2023 08:39:35 GMT

[View Forum Message](#) <> [Reply to Message](#)

```
EXECUTE BLOCK
RETURNS (TEXT_EXCEPTION VARCHAR(1024))
AS
BEGIN
BEGIN

end';
END
WHEN ANY DO
BEGIN
:TEXT_EXCEPTION = CAST(RDB$ERROR(MESSAGE) AS VARCHAR(512) CHARACTER SET
NONE);
```

```
SUSPEND;  
END  
END
```

```
EXC$CHECK_DATA
```

```
At block line: 1, col: 24
```

```
At block line: 6, col: 1
```

STATEMENT

Posted by [Dmitry Kovalenko](#) on Mon, 10 Jul 2023 08:57:42 GMT

[View Forum Message](#) <> [Reply to Message](#)

```
EXECUTE BLOCK  
RETURNS (TEXT_EXCEPTION VARCHAR(1024))  
AS  
BEGIN  
BEGIN  
EXECUTE STATEMENT _win1251 'execute block as begin EXCEPTION EXC$CHECK_DATA  
  
END  
WHEN ANY DO  
BEGIN  
:TEXT_EXCEPTION = RDB$ERROR(MESSAGE);  
SUSPEND;  
END  
END
```


EXC\$CHECK_DATA

At block line: 1, col: 24

At block line: 6, col: 1

EXC\$CHECK_DATA

At block line: 1, col: 24

Cannot transliterate character between character sets

At block line: 10, col: 1

EXC\$CHECK_DATA

At block line: 1, col: 24
