Posted by keepermode on Tue, 29 Oct 2024 08:48:02 GMT

View Forum Message <> Reply to Message

Grantor, Grant, With Grant, Deny

EXEC sp_msforeachdb 'USE [?];

IF DB_NAME() NOT IN (''master'', ''model'', ''msdb'', ''tempdb'')
    SELECT DB_NAME() AS [DB_NAME], RP.name AS [Role_NAME],
 UP.default_schema_name AS [User_Schema] --, --sys.schemas
    FROM sys.database_role_members AS R
    INNER JOIN sys.database_principals AS UP
      ON UP.principal_id = R.member_principal_id
    INNER JOIN sys.database_principals AS RP
      ON RP.principal_id = R.role_principal_id
    ORDER BY RP.name, UP.name
'
GO

SELECT table_name, table_type, TABLE_SCHEMA
          FROM information_schema.table

select DISTINCT permission_name from sys.database_permissions

-- alter, control, Permission, Delete, Insert, References, Select, Update, Take owneship, Vew
change tracking, Vew definition

File Attachments
1)   , downloaded 564

```
times
```

Posted by keepermode on Tue, 29 Oct 2024 18:55:43 GMT

View Forum Message <> Reply to Message

Posted by keepermode on Wed, 30 Oct 2024 06:40:54 GMT

View Forum Message <> Reply to Message

DB_NAME , Role_NAME , User_Schema , table_name , table_type , TABLE_SCHEMA

Posted by BlackEric on Thu, 31 Oct 2024 08:28:07 GMT

View Forum Message <> Reply to Message

Declare @T Table ([DB_NAME] nvarchar(128), [Role_NAME] nvarchar(128), [User_Schema] nvarchar(128))
Insert @T
EXEC sp_msforeachdb 'USE [?];

IF DB_NAME() NOT IN (''master'', ''model'', ''msdb'', ''tempdb'')
    SELECT DB_NAME() AS [DB_NAME], RP.name AS [Role_NAME],
 UP.default_schema_name AS [User_Schema] --, --sys.schemas
   FROM sys.database_role_members AS R
   INNER JOIN sys.database_principals AS UP
      ON UP.principal_id = R.member_principal_id
   INNER JOIN sys.database_principals AS RP
      ON RP.principal_id = R.role_principal_id
   ORDER BY RP.name, UP.name
'

Select * from @T t

left join
 information_schema.TABLES ist
on t.User_Schema = ist.TABLE_SCHEMA
GO

Permissions?

select permission_name, T.name AS Table_name, state_desc, type_desc, U.name, major_id
from sys.database_permissions P join sys.tables T ON P.major_id = T.object_id join sysusers
U ON U.uid = P.grantee_principal_id

select DISTINCT permission_name from sys.database_permissions

select permission_name, T.name AS Table_name, state_desc, type_desc, U.name, major_id
from sys.database_permissions P join sys.tables T ON P.major_id = T.object_id join sysusers
U ON U.uid = P.grantee_principal_id

Posted by BlackEric on Sat, 02 Nov 2024 13:35:06 GMT

```
Declare @Tt Table ([DB_NAME] nvarchar(128), [Role_NAME] nvarchar(128), [User_Schema]
nvarchar(128), [User_Schema_Id] int)
Insert @Tt
EXEC sp_msforeachdb 'USE [?];

IF DB_NAME() NOT IN (''master'', ''model'', ''msdb'', ''tempdb'')
   SELECT DB_NAME() AS [DB_NAME],  UP.name AS [Role_NAME],
 UP.default_schema_name AS [User_Schema], sc.schema_id
   FROM sys.database_role_members AS R
 INNER JOIN sys.database_principals AS UP
     ON UP.principal_id = R.member_principal_id
 Left JOIN sys.schemas sc
  on UP.default_schema_name = sc.[name]
   ORDER BY UP.name
'

Select tt.DB_NAME, tt.Role_NAME, tt.User_Schema, tt.User_Schema_Id, P.permission_name,
T.name AS Table_name, P.state_desc, T.type_desc, U.name,  P.major_id  from @Tt tt
left join sys.TABLES st
 on tt.User_Schema_Id = st.schema_id
join sys.database_permissions P
 on p.major_id = st.object_id
join  sys.tables T
 ON P.major_id = T.object_id
join  sysusers U
 ON U.uid = P.grantee_principal_id
GO
```

Posted by keepermode on Tue, 05 Nov 2024 12:56:58 GMT