
Posted by [marcodor](#) on Fri, 21 Feb 2025 09:49:12 GMT

[View Forum Message](#) <> [Reply to Message](#)

```
select
  b.id, b.fdate,
  c.code, c.name
from ta_bundle b
left join ta_entity c on (c.id = b.entity_id)
rows 1000 to 1010
```

Select Expression

- > First N Records
- > Skip N Records
- > Nested Loop Join (outer)
 - > Table "TA_BUNDLE" as "B" Full Scan
 - > Filter
 - > Table "TA_ENTITY" as "C" Access By ID
 - > Bitmap
 - > Index "PK_TA_ENTITY" Unique

Scan

TA_BUNDLE - 1010

TA_ENTITY - 1010

```
select
```

```
b.id, b.fdate,  
c.code, c.name  
from ta_bundle b  
left join lateral (  
  select c.code, c.name  
  from ta_entity c  
  where c.id = b.entity_id) c on true  
rows 1000 to 1010
```

```
select  
  b.id, b.fdate,  
  -- ? c.code  
  (select c.name from ta_entity c where c.id = b.entity_id)  
from ta_bundle b  
rows 1000 to 1010
```

Posted by [marcodor](#) on Fri, 21 Feb 2025 11:27:45 GMT
[View Forum Message](#) <> [Reply to Message](#)

```
with b as (  
  select  
    b.id, b.fdate, b.entity_id  
  from ta_bundle b  
  rows 1000 to 1010  
)  
select  
  b.id, b.fdate,  
  c.code, c.name  
from b  
left join ta_entity c on (c.id = b.entity_id)
```

Posted by [SD](#) on Fri, 21 Feb 2025 11:38:38 GMT
[View Forum Message](#) <> [Reply to Message](#)

Posted by [marcodor](#) on Fri, 21 Feb 2025 11:52:08 GMT
[View Forum Message](#) <> [Reply to Message](#)

999

Posted by [SD](#) on Fri, 21 Feb 2025 21:59:19 GMT
[View Forum Message](#) <> [Reply to Message](#)
